

## PIT es Set1s-5ns

400453



PITestop, E-STOP/contact block incl. surface mount housing, set consisting of E-STOP pushbutton with E-STOP symbol and logo and contact block 2 N/C, with M12 connection 5-pin.

## Technical details

General data	
Approval:	CE
Self-monitored:	yes
Technical data	
Electrical data	
Min. contact current:	1 mA
Emergency stop	
Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi
Environmental data	
Ambient temperature:	-25 - 55 °C
Pollution degree clear.&creep.:	3
Mechanical data	
Mounting position:	any
Connection terminal:	M12
Height dimension:	103 mm
Width dimension:	72 mm
Depth dimension:	85 mm
Net weight:	178 g
Gross weight:	215 g

Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002034